

AERATION CIRCULATION 50 HZ


Water in AIR / AIR in Water

BRIO-OX 47

BRIO-OX 47 is a surface aerator designed for great circulation, degassing and aeration effect. The powerful motors with which the aerator is supplied are the big brothers of the BRIO-OX range. This innovative system is the ideal solution for the oxygenation and degassing of huge volumes of water at the best efficiency rates and lowest energy consumption. Quick destratification of water basins, tanks and ponds is implemented thanks to the massive action of this cost-effective machine, which helps prompt recovery of the environmental balance.

PLUS

- › Lightweight, easy to handle and to move from tank to tank or from pond to pond
- › Sturdy and durable
- › Suitable for use in freshwater as well as in salt water
- › Conveyor available to direct the flow in order to obtain a longer direct effect
- › Floating and dock mount support versions available



SINGLE PHASE 230 V	THREE PHASE 400 V	NOM. POW. HP	NOM. POW. KW	AMPERAGE SINGLE PHASE	AMPERAGE THREE PHASE	CAPACITY L/MIN.	R.P.M./1"	WEIGHT KG
BRIO-OX 47 1.5 M BRIO-OX 47 P 2 M	BRIO-OX 47 1.5 T BRIO-OX 47 2 T BRIO-OX 47 P 3 T	1.5 2 3	1.1 1.5 2.2	7.5 10	2.5 3.2 4.8	3100 3700 5400	2800 2800 2800	16.5 20/17.5 20



SUPPORTS



FLOATING INSTALLATION

Light weight and easy to install, for standard aquaculture applications.



DOCK MOUNTING INSTALLATION

Usefull for lake de-icing, weeds/algae removal and destratification.



MADE IN ITALY



ACQUA&CO S.R.L

Via Augera, 5/A 42023 Cadelbosco di Sopra (RE) - Italia
Tel. +39 0522 918701 - Fax +39 0522 918790
info@acquaeco.com

